

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 703 728 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
11.09.2002 Bulletin 2002/37

(51) Int Cl.7: **A23D 9/00**

(86) International application number:
PCT/US94/06352

(21) Application number: **94919379.1**

(87) International publication number:
WO 95/000036 (05.01.1995 Gazette 1995/02)

(22) Date of filing: **10.06.1994**

(54) **POURABLE CANOLA OIL FOR FOOD APPLICATIONS**

VERGIESSBARES CANOLA-ÖL UND DESSEN VERWENDUNG IN NAHRUNGSMITTELN

HUILE DE COLZA COULANTE A USAGE ALIMENTAIRE

(84) Designated Contracting States:
BE DE DK FR GB NL

(56) References cited:
WO-A-93/06714 WO-A-93/17566
CA-A- 835 334

(30) Priority: **17.06.1993 US 78384**

(43) Date of publication of application:
03.04.1996 Bulletin 1996/14

(73) Proprietor: **CARGILL, INCORPORATED**
Wayzata, MN 55440 (US)

(72) Inventors:
• **COVINGTON, Robert, Melvin, Jr.**
Rossville, Tennessee 38066 (US)
• **UNGER, Ernie, H.**
Idaho Falls, ID 83404 (US)

(74) Representative: **Fisher, Adrian John et al**
CARPMAELS & RANSFORD
43 Bloomsbury Square
London WC1A 2RA (GB)

- NTIS TECH NOTES, 1992, SPRINGFIELD, VA US page 618 'Food flavor enhanced by lowering vegetable oil acid'
- JOURNAL OF THE AMERICAN OIL CHEMISTS' SOCIETY., vol.70, no.10, 1993, CHAMPAIGN US pages 983 - 988 K. WARNER ET AL. 'Frying stability of soybean and canola oils with modified fatty acid compositions'
- FOOD TECHNOLOGY, vol.45, no.2, 1991, CHICAGO US pages 95 - 96 ROY A. CARR 'Development of deep-frying fats'
- CANADIAN INSTITUTE OF FOOD SCIENCE AND TECHNOLOGY JOURNAL, vol.17, no.4, 1984, CA pages 187 - 194 S.G. STEVENSON ET AL. 'Performance of canola and soybean fats in extended frying'
- DATABASE WPI Week 9249, Derwent Publications Ltd., London, GB; AN 92-399446 & CS,A,748 889 (PALMA SP) 17 June 1992
- DATABASE WPI Week 7735, Derwent Publications Ltd., London, GB; AN 77-61867Y & JP,A,52 085 206 (ASAHI ELECTROCHEMIND KK) 15 July 1977
- FOOD MARKETING & TECHNOLOGY, vol.6, no.2, 1992 pages 20 - 24 'Storage and performance stability of vegetable oils'
- INFORM, vol.3, no.4, 1992, CHAMPAIGN US page 543 ZENIA J. HAWRYSH 'Use of canola oil for snacks and convenience foods'

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 703 728 B1

Description

[0001] The present application relates to a pourable partially hydrogenated canola oil low in saturated fatty acids and low in trans fatty acids having improved flavor and performance attributes especially suitable for food applications.

BACKGROUND

[0002] Canola oil has the lowest level of saturated fatty acids of all vegetable oils. As consumers become more aware of the health impact of lipid nutrition, consumption of canola oil in the U.S. has increased. However, generic canola oil has limited use in deep frying operations, an important segment of the food processing industry, due to its instability. Oil extracted from the seed of commercial canola (rapeseed) varieties contains a relatively high (8%-13%) linolenic acid content ($C_{18:3}$) (ALA). Linolenic acid has been reported to oxidize faster than other fatty acids. Linoleic and linolenic acids have been suggested as precursors to undesirable odor and flavor development in foods. Generic canola oil is unstable and easily oxidized during cooking, which in turn compromises the sensory characteristics of foods cooked in such oils. It also develops unacceptable off odors and rancid flavors during storage.

[0003] Hydrogenation can be used to improve performance attributes by lowering the amount of linoleic and linolenic acids in the oil. In this process the oil increases in saturated and trans fatty acids, both undesirable when considering health implications. Furthermore pourability of oils is reduced. This latter problem has been overcome by partial hydrogenation of zero-erucic acid rapeseed oil which reduced the levels of linolenic and linoleic acid without reducing pourability of the oil (CA-835334). Bansal et al., Journal of Food Science, Vol. 47, p. 1338 (1982) describe the effect of hydrogenation under selective and nonselective conditions using commercial nickel catalysts on the chemical composition of canola oil. Generally selective hydrogenation conditions resulted in a higher level of *trans* isomers. Research has shown that diets high in saturated fats increase low density lipoproteins, which promote the deposition of cholesterol on blood vessels. More recently, dietary consumption of foods high in trans fatty acids have also been linked to increased serum cholesterol content.

[0004] A canola oil having improved stability in its flavor and performance attributes for use in food operations is needed. In particular, a partially hydrogenated canola oil having improved frying performance but with low saturated fatty acid content and low trans fatty acid content is desired. The present invention provides such an oil.

SUMMARY OF THE INVENTION

[0005] The present invention provides an oil comprising a partially hydrogenated canola oil having a maximum saturated fatty acid content of about 9.6%, and a maximum trans fatty acid content of about 22.1%. The oil of the present invention also has fry stability as demonstrated by lower off-flavor development compared to the industry standard frying shortening. The present invention further comprises a method of improving the flavor of fried foods comprising frying the foods in the oil of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0006] The present invention provides a hydrogenated canola oil low in saturated fatty acids and in *trans* fatty acids having superior stable flavor and frying attributes when compared to known canola frying oils.

[0007] In the context of this disclosure, a number of terms are used. Saturated fatty acids include myristic ($C_{14:0}$), palmitic ($C_{16:0}$), stearic ($C_{18:0}$), arachidic ($C_{20:0}$), behenic ($C_{22:0}$), and lignoceric ($C_{24:0}$) acids. *Trans* fatty acids include any *trans* isomer of a C_{14} through C_{24} fatty acid.

[0008] As used herein, "functionality" or "performance attributes" means properties or characteristics of the canola oil and includes flavor stability, fry stability, and oxidative stability.

[0009] Oxidative stability relates to how easily components of an oil oxidize which creates off-flavors in the oil, and is measured by instrumental analysis such as Accelerated Oxygen Method (AOM) American Oil Chemists' Society Official Method Cd 12-57 for Fat Stability: Active Oxygen Method (re'vd 1989), and Rancimat (Laubli, M. W. and Bruttel, P. A., JOACS 63:792-795 (1986)). The degree of oxidative stability is rated as the number of hours to reach a peroxide value of 100.

[0010] Fry stability relates to the resistance to degeneration of the oil during frying. "Fry life" is the time it takes for the flavor of a product fried in an oil to degrade to give a set score using sensory analysis. Improved stability characteristics of the oil are reflected in improved flavors of the foods prepared in the oil. Flavor stability is determined by periodic sensory analysis of foods fried in the oil by a trained sensory panel. Oils for restaurants, hospitals, and large institutions primarily are used for frying foods and require fry stability.

[0011] A sensory panel refers to those individuals involved in the sensory evaluation of the edible food product. The panelists are prescreened to detect the flavor differences in the particular product tested. The panel is trained in sensory

descriptions. The panel provides qualitative and quantitative scores for the sensory evaluation which are referenced against calibrated standards. The results of the panel are reproducible. "Canola" refers to rapeseed (*Brassica*) which has an erucic acid (C_{22:1}) content of at most 2 percent by weight based on the total fatty acid content of a seed, preferably at most 0.5 percent by weight and most preferably essentially 0 percent by weight and which produces, after crushing, an air-dried meal containing less than 30 micromoles (μmol) of glucosinolates per gram of defatted (oil-free) meal.

[0012] The oil of the present invention is designated IMC 983. IMC 983 is a refined, bleached, partially hydrogenated and deodorized pourable canola oil. This oil is liquid and has no solid fats at 10°C or above. IMC 983 is made by partially hydrogenating a starting oil designated as IMC 129. IMC 129 oil is produced from *Brassica napus* plant line, a Spring canola variety, designated IMC 129. It is described in detail in U.S. PVP Certificate No. 9100151. The IMC 129 variety possesses high oleic acid in the seed oil. This oil has an oleic acid content of about 75 to 80% by weight, a linoleic acid content of about 5 to 10% by weight, a linolenic acid content of less than 7% by weight, and an erucic acid content of less than 2% by weight. The oil has an iodine value of about 90 to 110.

[0013] Hydrogenation is done at a temperature of from about 120°C to about 170°C. Standard batch hydrogenation equipment featuring internal steam heating and water cooling is used. A selective nickel supported catalyst such as Nysel 325 (Engelhard, Cleveland, OH), G-95 (United Catalyst, Louisville, KY), Calcicat 472 (Mallinkrodt, Erie, PA), or Pricat 9920 (Unichem, Emmerich, Germany) may be used. The IMC 129 starting oil is hydrogenated to a refractive index of approximately 1.4593 at 48°C and an iodine value of between about 77 and 87.

[0014] The resulting canola oil of the present invention (IMC 983) has a maximum saturated fatty acid content of about 9.6% and a maximum *trans* fatty acid content of about 22.1%. It also has a minimum oxidative stability of about 176 AOM hours in the absence of antioxidants. It has an oleic acid content of about 83.6% and an iodine value of about 82 to about 84.

[0015] Under extended frying conditions, the IMC 983 oil is significantly lower than commercial frying oils in the development of off-flavors. Trained sensory panelists found food fried in IMC 983 significantly better than that cooked in commercial frying oil in 6 of 12 categories of sensory characteristics for rating off-flavor development.

[0016] The oil of the present invention is especially suitable for use in food applications, in particular for frying foods, due to its superior oxidative stability and fry stability. Due to its low levels of saturated fatty acids and *trans* fatty acids, it is especially desirable for human consumption over heavily hydrogenated frying oils. Common additives can be added to the oil of the present invention such as a stabilizer, flavoring, emulsifier, anti-spattering agent, colorant, or antioxidant.

[0017] The present invention is further defined in the following Examples, in which all parts and percentages are by weight and degrees are Celsius, unless otherwise stated. It should be understood that these Examples, while indicating preferred embodiments of the invention, are given by way of illustration only.

EXAMPLE 1

[0018] The fatty acid composition of the IMC 129 starting oil which was hydrogenated is provided in Table 1. The iodine value of the starting oil was 98.6. The refractive index of the starting oil was 1.4608 at 48°C.

Table 1

Fatty Acid Composition of the Starting Oil										
Starting Oil	Fatty Acid Composition (%)									
	C _{14:0}	C _{16:0}	C _{18:0}	C _{18:1}	C _{18:2}	C _{18:3}	C _{22:0}	C _{22:1}	C _{24:0}	Sats ¹
IMC 129	0	3.6	2.2	75.9	9.1	5.4	0.4	0.2	0.2	7.01

¹Total content of saturated fatty acids

[0019] The hydrogenation was conducted in a standard batch hydrogenation reactor at a pressure varying between 200 and 220 kPa. The oil was heated to an initial gassing temperature of 145°C and the hydrogenation was conducted over a period of approximately 24 min. The nickel catalyst used was Nysel 325. The oil was hydrogenated to a refractive index of 1.4593 at 48°C.

[0020] After the hydrogenation 80 to 100 ppm citric acid dissolved in propylene glycol was added to the oil prior to filtration to help in the removal of nickel and iron from the oil. The hydrogenated oil was deodorized under standard deodorization conditions for canola. Fatty acid composition of the hydrogenated and deodorized IMC 983 oil is in Table 2. The IMC 983 oil was clear and brilliant at 40°C. Other physical properties of the IMC 983 oil are described in Table 3.

Table 2

Fatty Acid Composition (%) of IMC 983 Oil	
Fatty Acid	%
C _{14:0}	0
C _{16:0}	3.8
C _{18:0}	4.5
C _{18:1}	83.6
C _{18:2}	4.1
C _{18:3}	0.2
C _{20:0}	0.7
C _{22:0}	0.4
C _{24:0}	0.2
Sats ¹	9.6
Trans ²	22.1

¹Total content of saturated fatty acids²Total content of *trans* fatty acids

Table 3

Physical Measurements of IMC 983	
Parameter	
Refractive Index at 48°C	1.4593
Free Fatty Acids (%)	0.01
Lovibond Color, 5 1/4"	0.3 Red
Iodine Value	82.0
Trans Isomers (%)	22.1
AOM hours	176

EXAMPLE 2

[0021] The oil of Example 1 was subjected to further testing to determine frying stability as measured by off-flavor development.

[0022] French fry preparation in restaurants occurs in two steps. Potatoes are cut and partially cooked, a process called par frying, and frozen by a food processor for delivery to individual restaurants. The frozen par fried french fries are then recooked, a process called finish frying, at the restaurant immediately prior to service. IMC 983 oil of Example 1 was tested against 189LC, a leading industry standard frying oil, a partially hydrogenated soybean oil available from Interstate Foods Corp., 3800 S. Morgan Street, Chicago, IL 60609 for finish frying of french fries. The quality of the french fries finish fried in each oil were then evaluated to determine the fry stability of each oil for restaurant frying.

[0023] The IMC 983 and 189LC oils were tested in a 21-day fry test which simulated commercial food service conditions. Twenty-three (23) kg of each oil was placed into each fryer (FryMaster MACH352SD, Frymaster Corp., Welbilt Co., Shreveport, LA) and fried according to a schedule which simulates frying in fast food restaurants (Table 4). The par fry french fries used for finish frying with 189LC were produced in partially hydrogenated soybean oil. The par fry french fries used for finish frying with IMC 983 were produced in partially hydrogenated canola oil. Tallow flavoring was added to both par fry oils to standardize test conditions.

Table 4

Frying Schedule for Oil Testing		
Time	Activity	Baskets
6:00 a.m.	Turn on fryers	0
6:00 a.m.-8:00 a.m.	Idle fryers at set point	0
8:00 a.m.-9:00 a.m.	Fry baskets every 5 min. Fry 2 baskets twice and then 1 basket the rest of the hour	14
9:00 a.m.-10:00 a.m.	Fry baskets every 5 min. Fry 2 baskets twice and then 1 basket the rest of the hour	14
10:00 a.m.-10:30 a.m.	Fry 2 baskets every 5 min.	12
10:30 a.m.-11:00 a.m.	Idle fryers	0
11:00 a.m.-1:00 p.m.	Fry 1 basket every 5 min.	24
1:00 p.m.-1:30 p.m.	Idle fryers	0
1:30 p.m.-6:00 p.m.	Fry 1 basket every 7-1/2 min.	36
6:00 p.m.-6:30 p.m.	Idle fryers	0
6:30 p.m.-8:00 p.m.	Fry 1 basket every 4-1/2 min.	20

[0024] The par fried french fries were finish fried in the IMC 983 and 189LC oils using a fry time of 3 minutes. The oil temperature was maintained at 171°C. Fresh oil was added at 10:30 a.m. (after high volume frying), 6:00 p.m. (after high volume frying) and 8:00 p.m. (after filtration) to make up for oil absorption into the french fries. Each frying oil was filtered nightly with 0.23 kg of fresh Magnesol XL filter media available from Dallas Group, Jeffersonville, IN, utilizing the Prince Castle filter available from Prince Castle, Carole Stream, IL. A total of 116 baskets (85.7 kg) of french fries were finish fried daily. A total of 1800 kg of french fries were cooked in each oil over the entire test.

[0025] The french fries were checked daily for color, internal texture, external texture, and flavor. Color measurements were made by an Agtron instrument. Internal texture, external texture, aroma, and flavor of the french fries were determined by a trained sensory panel. Over the entire duration of the fry test, the panel failed to detect any significant differences in the internal or external texture of the french fries. However, the french fries which had been finish fried in IMC 983 were significantly better than those cooked in 189LC in 6 of the 12 categories where off-flavor development was lower (Table 5). IMC 983 was not significantly different from 189LC in the other categories. The sensory panel concluded that the french fries cooked in the 189LC oil would be judged unacceptable by the average food service manager starting on day 16, while the french fries cooked in IMC 983 were acceptable through the entire 21-day test.

Table 5

Characteristics of French Fries Cooked in IMC 983 Oil	
Sensory Characteristic	Performance of IMC 983*
Overall Intensity - Aroma	Not significantly different
Fried Aroma	Not significantly different
Tallow Aroma	Lower than 189LC
Burnt Aroma	Not significantly different
Atypical Aroma	Not significantly different
Overall Intensity - Flavor	Not significantly different
vegetable Oil Flavor	Lower than 189LC
Burnt Flavor	Lower than 189LC
Painty Flavor	Not significantly different

*Significant at 95% Confidence Interval

EP 0 703 728 B1

Table 5 (continued)

Characteristics of French Fries Cooked in IMC 983 Oil	
Sensory Characteristic	Performance of IMC 963*
Atypical Flavor	Lower than 189LC
Overall Intensity - Aftertaste	Lower than 189LC
Atypical Aftertaste	Lower than 189LC

*Significant at 95% Confidence Interval

[0026] Measurement of french fry color and free fatty acid show that both oils were comparable (Table 6). No significant differences exist between the french fries for either of these characteristics.

Table 6

French Fry Color and Free Fatty Acid Content of Frying Oils				
Analysis	Fried Color		Free Fatty Acid, %	
Days/Oil	189LC	IMC 983	189LC	IMC 983
1	60.70	60.30	0.26	0.28
2	51.50	64.40	0.49	0.51
3	59.80	62.80	0.71	0.82
4	50.80	62.10	1.09	1.16
5	59.90	64.40	1.31	1.53
6	50.40	60.00	1.60	1.96
7	61.10	63.80	1.90	2.22
8	62.00	62.30	2.20	2.90
9	61.60	58.80	3.00	3.30
10	59.60	61.20	3.23	3.99
11	60.20	62.30	3.40	4.51
12	58.60	59.90	3.88	5.33
13	55.30	58.80	4.59	5.86
14	51.70	59.60	4.85	6.31
15	53.60	58.90	5.02	6.69
16	53.20	54.10	5.46	7.20
17	53.10	56.40	5.67	7.41
18	55.20	58.00	5.82	7.41
19	56.20	58.20	6.04	7.79
20	50.80	55.50	7.16	8.36
21	52.20	55.40	7.08	8.22

[0027] Analysis of the oil content (%) of the finish fry french fries and the amount of makeup oil (kg) required daily show that french fries cooked in IMC 983 absorbed 6% less oil (Table 7). Conversely, each pound of IMC 983 oil fried 1.87 more pounds of french fries than each pound of 189LC oil.

Table 7

Oil Absorption in Finish Fried French Fries				
Oil Absorption	Oil Content, %		Makeup Oil, kg	
Days/Oils	189LC	IMC 983	189LC	IMC 983
1	17.00	16.00	5.8	3.0
2	17.30	15.20	3.8	3.4
3	15.50	14.80	5.0	4.2
4	15.80	15.30	5.4	3.9
5	15.30	15.30	5.9	4.5
6	15.40	15.30	4.9	3.9
7	14.70	13.90	5.0	4.4
8	15.70	15.50	4.2	3.4
9	15.10	15.60	4.9	4.0
10	15.50	16.00	5.3	4.2
11	15.10	15.30	4.2	3.9
12	15.60	14.60	4.5	4.5
13	16.20	16.10	4.2	3.8
14	16.80	14.90	4.1	3.8
15	16.30	14.70	4.2	4.2
16	19.50	15.30	4.0	3.6
17	16.00	14.70	3.7	3.9
18	14.90	15.00	3.6	3.9
19	18.00	16.10	3.9	3.6
20	16.20	13.90	4.2	4.2
21	15.70	15.20	3.0	2.8
Average	16.08	15.18	N/A	N/A
Total	N/A	N/A	93.8	81.1

[0028] In addition to the stability characteristics described above, IMC 983 also has lower levels of saturated fatty acids and *trans* fatty acids (Table 8).

Table 8

Fatty Acid Composition (%) of Frying Shortening		
Fatty Acid	IMC 983	189LC
C _{14:0}	0	0
C _{16:0}	3.8	11.7
C _{18:0}	4.5	10.1
C _{18:1}	83.6	65.2
C _{18:2}	4.1	9.5
C _{18:3}	0.2	0.2
C _{20:0}	0.7	0.3

Table 8 (continued)

Fatty Acid Composition (%) of Frying Shortening		
Fatty Acid	IMC 983	189LC
C _{22:0}	0.4	0.2
C _{24:0}	0.2	0.1
Sats ¹	9.6	22.6
Trans ²	22.1	43.4

¹Total content of saturated fatty acids²Total content of trans fatty acids**EXAMPLE 3**

[0029] IMC 129 oil and a generic canola oil of the Alto variety, designated Oil A, were hydrogenated to an iodine value of approximately 83. The fatty acid composition and iodine values of the IMC 129 and Oil A starting oils is provided in Table 9.

Table 9

Fatty Acid Composition of the Starting Oil							
Starting Oil	Fatty Acid Composition (%)						
	C _{14:0}	C _{16:0}	C _{18:0}	C _{18:1}	C _{18:2}	C _{18:3}	I.V. ¹
IMC 129	0	3.6	2.0	75.7	9.5	6.2	94.2
Oil A	0	4.0	2.0	62.5	18.3	7.7	109.8

¹I.V. = Iodine Value

[0030] The hydrogenation was conducted in a stirred batch hydrogenation reactor at a pressure of about 210 kPa. The oil was heated to an initial gassing temperature of 150°C and the hydrogenation was conducted using a nickel catalyst, 0.2% Nysel 325. The oil was hydrogenated to an iodine value of about 83.

[0031] After the hydrogenation 80 to 100 ppm citric acid dissolved in propylene glycol was added to the oil prior to filtration to help in the removal of nickel and iron from the oil. The hydrogenated oil was deodorized under standard deodorization conditions for canola. Fatty acid composition of the hydrogenated and deodorized oils is in Table 10. The hydrogenated IMC 129 oil was designated IMC 983. Other physical properties of the hydrogenated oils are described in Table 11. Solid fat index profile was determined as in AOAC Official Method Cd 10-57 for solid fat index, revised 1989, American Oil Chemists Society.

Table 10

Fatty Acid Composition		
Fatty Acid	%	
Oil	IMC 983	Oil A
C _{14:0} , %	0	0
C _{16:0} , %	3.7	4.0
C _{18:0} , %	4.0	5.2
C _{18:1} , %	83.8	79.2
C _{18:2} , %	4.0	5.3
C _{18:3} , %	0.5	0.3
C _{20:0} , %	0.8	0.8
C _{22:0} , %	0.4	0.4

Table 10 (continued)

Fatty Acid Composition		
Fatty Acid	%	
Oil	IMC 983	Oil A
C _{24:0} , %	0.2	0.2
Sats ¹ , %	9.1	10.6

¹Total content of saturated fatty acids

Table 11

Physical Measurements		
Parameter	IMC 983	Oil A
Iodine Value	83.6	83.1
<i>Trans</i> Isomers, %	16.5	23.2
Hydrogenation Time min.	30	60
Solid Fat Index, %		
10.0°C	0.0	4.4
21.1°C	0.0	0.7
26.7°C	0.0	0.0
33.3°C	0.0	0.0

[0032] The unique physical characteristic of IMC 983 (no solids at 10.0°C, low trans isomers and greater than 83% C_{18:1}) was only obtained by hydrogenating an oil with the fatty acid composition of IMC 129. As seen from Tables 10 and 11, the hydrogenation of a generic canola oil, such as Oil A, did not result in a product with these characteristics.

Claims

1. A pourable partially hydrogenated canola oil having a maximum saturated fatty acid content of about 9.6%, a maximum trans fatty acid content of about 22.1% and a minimum oxidative stability of about 176 AOM hours in the absence of added antioxidants.
2. The oil of claim 1, wherein said oil is suitable for frying foods for at least 21 continuous days for at least 14 hours per day.
3. The oil of claim 1 to which has been added at least one additive selected from the group consisting of a stabilizer, flavoring, emulsifier, anti-spattering agent, colorant, or antioxidant.
4. The oil of claim 1, said oil having an oleic acid content (C_{18:1}) of about 83.6%.
5. The oil of claim 1, said oil having the following characteristics :

Fatty Acid Composition	
Fatty Acid	%
Oil	IMC 983
C _{14:0} , %	0
C _{16:0} , %	3.7
C _{18:0} , %	4.0

(continued)

Fatty Acid Composition	
Fatty Acid	%
Oil	IMC 983
C _{18:1} , %	83.8
C _{18:2} , %	4.0
C _{18:3} , %	0.5
C _{20:0} , %	0.8
C _{22:0} , %	0.4
C _{24:0} , %	0.2
Sats ¹ , %	9.1

¹Total content of saturated fatty acids

6. The oil of claim 1, said oil having an iodine value of about 82 to about 84.
7. The oil of claim 1, said oil having 0% solid fat at 10°C.
8. A method of improving the flavor of fried foods comprising frying the foods in the oil of claim 1.
9. A pourable partially hydrogenated canola oil as defined in claim 1 obtainable by hydrogenation of IMC129 oil at a temperature of from about 120°C to about 170°C, to a refractive index of approximately 1.4593 at 48°C and an iodine value of between 77 and 87.

Patentansprüche

1. Gießbares teilhydriertes Canola-Öl mit einem maximalen Gehalt an gesättigten Fettsäuren von etwa 9,6 %, einem maximalen Gehalt an trans-Fettsäuren von etwa 22,1 % und einer maximalen Oxidationsstabilität gemäß AOM von etwa 176 Stunden in der Abwesenheit von zugegebenen Antioxidantien.
2. Öl nach Anspruch 1, wobei das Öl zum Braten bzw. Fritieren von Lebensmitteln für mindestens 21 aufeinanderfolgenden Tage während mindestens 14 Stunden pro Tag geeignet ist.
3. Öl nach Anspruch 1, dem mindestens ein Zusatzstoff zugegeben wurde, der aus der aus Stabilisatoren, Aromen, Emulgatoren, Mitteln zur Verhinderung einer Spritzerbildung, Farbstoffen oder Antioxidantien bestehenden Gruppe ausgewählt ist.
4. Öl nach Anspruch 1, wobei das Öl einen Ölsäuregehalt (C_{18:1}) von etwa 83,6 % aufweist.
5. Öl nach Anspruch 1 mit den folgenden Eigenschaften: Fettsäurezusammensetzung

Fettsäurezusammensetzung	
Fettsäure	%
Öl	IMC 983
C _{14:0} , %	0
C _{16:0} , %	3,7
C _{18:0} , %	4,0
C _{18:1} , %	83,8
C _{18:2} , %	4,0

EP 0 703 728 B1

(fortgesetzt)

Fettsäurezusammensetzung	
Fettsäure	%
Öl	IMC 983
C _{18:3} , %	0,5
C _{20:0} , %	0,8
C _{22:0} , %	0,4
C _{24:0} , %	0,2
Gesätt. ¹ , %	9,1

¹Gesamtgehalt von gesättigten Fettsäuren

6. Öl nach Anspruch 1, wobei das Öl eine Jodzahl von etwa 82 bis etwa 84 aufweist.
7. Öl nach Anspruch 1, wobei das Öl 0 % festes Fett bei 10 °C aufweist.
8. Verfahren zur Verbesserung des Aromas von gebratenen bzw. fritierten Lebensmitteln, das das Braten bzw. Fritieren der Lebensmittel in dem Öl nach Anspruch 1 umfaßt.
9. Gießbares teilhydriertes Canola-Öl nach Anspruch 1, das durch Hydrieren von IMC 129-Öl bei einer Temperatur von etwa 120 °C bis etwa 170 °C bis zu einem Brechungsindex von etwa 1,4593 bei 48 °C und einer Jodzahl von zwischen 77 und 87 erhältlich ist.

Revendications

1. Huile de colza hydrogénée partiellement coulante ayant une teneur maximale en acides gras saturés d'environ 9,6%, une teneur maximale en acides gras trans d'environ 22,1% et une stabilité minimale à l'oxydation d'environ 176 heures par la méthode AOM, en l'absence d'antioxydants ajoutés.
2. Huile selon la revendication 1, dans laquelle ladite huile convient pour la friture des aliments pendant au moins 21 jours continus à raison d'au moins 14 heures par jour.
3. Huile selon la revendication 1 à laquelle on a ajouté au moins un additif choisi dans le groupe constitué par un stabilisant, un arôme, un émulsifiant, un anti-éclaboussant, un colorant ou un antioxydant.
4. Huile selon la revendication 1, ladite huile ayant une teneur en acide oléique (C_{18:1}) d'environ 83,6%.
5. Huile selon la revendication 1, ladite huile ayant les caractéristiques suivantes :

Composition en acides gras	
Acide gras	%
Hulle	IMC 983
C _{14:0} , %	0
C _{16:0} , %	3,7
C _{18:0} , %	4,0
C _{18:1} , %	83,8
C _{18:2} , %	4,0
C _{18:3} , %	0,5
C _{20:0} , %	0,8

(suite)

Composition en acides gras	
Acide gras	%
Huile	IMC 983
C _{22:0} , %	0,4
C _{24:0} , %	0,2
Saturés ¹ , %	9,1

¹Teneur totale en acides gras saturés

6. Huile selon la revendication 1, ladite huile ayant un indice d'iode d'environ 82 à environ 84.

7. Huile selon la revendication 1, ladite huile ayant 0% de graisse solide à 10°C.

8. Procédé pour améliorer le goût d'aliments frits comprenant la friture des aliments dans l'huile selon la revendication 1.

9. Huile de colza hydrogénée partiellement coulante selon la revendication 1 pouvant être obtenue par hydrogénation d'huile IMC 129 à une température d'environ 120°C à environ 170°C, jusqu'à un indice de réfraction d'environ 1,4593 à 48°C et un indice d'iode compris entre 77 et 87.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.